

# ILLUSIONS LOOSE LAY

## Technical Specifications

Tile Size(mm)	EN 427	P: 177.8 x 1219.2/ T: 470 x 470
Total Thickness	EN 649	5.0 mm
Wearlayer Thickness(mm)	EN 428	0.5 (±0.05)
Peeling Strength of Layers	EN 431	Pass
Weight per Ctn	EN 430	P:18.7kg/box/ T:20kg/box
Packing	EN 427	10 Planks/box
Impact Sound Reduction	ISO 717-2	9dB
Dimension Stability	EN 434	Pass
Colour Fastness to Light	ISO 105 B02	>Grade 6
Static Indentation	EN 433	<0.1mm
Flexibility	EN 435	Pass
Abrasion Resistance	EN 660-2	Class T
Castor Chair Resistance	EN 425	Pass
Slip Resistance	EN 13893	>0.3
	DIN 51130(Australia)	R10[HIGH*]
Fire Rating	EN 13501-1	Bfl-S1
	ASTME 84	Class 1
Usage Category	EN 685	23/42
Resistance to Chemical	EN 423	Pass
Electrostatic Properties	EN 1815	< 2kv
Surface Treatment		PUR
Embossing	Regular/Deep	
Guarantee	15 Year Commercial	25 Year Residential

## Loose Lay Cargo Information

Thickness	Wear Layer	Width	Per CTN
5mm Plank	0.5mm	177.8 x 1219.2mm	10pcs (2.167sqm)
5mm Tile	0.5mm	470 x 470mm	10pcs (2.21sqm)